

# Pumping Appliance

## Base Vehicle

- 18T chassis – 4.425mm wheelbase.
- 320 horsepower.
- Front leaf rear air suspension.
- ZF tipmatic gearbox.

## Pump Capabilities

- Over 4000lpm LP output.
- Over 40 bar HP output.
- Simultaneous combined output ability.
- 2 hose reels mounted in either rear or mid lockers.

## Secondary Fire Fighting

- 250kg dry powder system.
- Additional dry powder reel front half locker.

## Stowage

- 8 locker spaces + through locker.
- Over 10,000L locker capacity.
- Flush fitting locker doors available (cost option).
- Bespoke locker arrangement to customer needs.
- BA blister on back of cab to provide BA seating opportunities.
- Full ergonomic stowage layout to be developed to suit kit.

## Optional Extras

- **CleanCab** : All BA sets stowed in a variety of available in locker stowage options. Reduced risk of carcinogens and toxin contact.
- **Flush Roller Shutter Doors**: Reduced maintenance due to minimised risk of accidental damage. Reduced risk of harm to public.
- **Stowage**: Options to have either suction hose, equipment boxes, or short ladder on NS beam. Option to relocate fuel tank to provide 2 full height mis lockers.
- **Lighting**: A wide range of lighting solutions for all markets worldwide.
- **Pump Options**: Bronze or Alloy construction, 1 or 2 collection heads, full flow meter installation, 7" or 12" screens or with the ePumpRC system that allows full pump control anywhere.

[\*\*Download PDF\*\*](#)